

Appl. No. 10/605,501
Amdt. dated November 10, 2005
Reply to Office action of August 15, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

- 1 (currently amended): A method of printing an image on a printing medium with an
5 inkjet printing device, the method comprising:
providing data representative of an original image;
calculating a total heat weighting value for the original image to indicate a degree of
heat accumulation for the original image;
comparing the total heat weighting value to R distinct reference values, R being an
10 integer greater than or equal to one;
selecting M image masks to be used to mask the original image, wherein a value of
M is chosen according to comparison results between the total heat weighting
value and the R reference values, M being an integer greater than or equal to
[[one]] three, the M image masks being generated according to the following
15 steps:
(a1) choosing every Mth nozzle to be included in a first mask;
(a2) repeating step (a1) for selecting a second mask through an (M-1)th mask,
wherein nozzles that were previously chosen to be included in other masks
are not included in any additional masks; and
20 (a3) choosing all remaining nozzles to be included in an Mth mask;
masking the original image with the M image masks to produce M sub-images; and
printing the M sub-images successively on the printing medium with a plurality of
nozzles for superimposing the M sub-images on the printing medium, whereby
the original image is printed on the printing medium.
25
- 2 (original): The method of claim 1 wherein selecting M image masks comprises reading
the M image masks from a table memory.

Appl. No. 10/605,501
Amdt. dated November 10, 2005
Reply to Office action of August 15, 2005

3-6 (cancelled).

7 (original): The method of claim 1 wherein the total heat weighting value is calculated
5 according to locations of the pixels to be printed and a heat weighting look-up table.

8 (original): The method of claim 1 wherein the total heat weighting value is a sum of
heat weighting values calculated for each row of nozzles contained in a printhead of
the inkjet printing device.
10

9 (original): The method of claim 8 wherein the total heat weighting value is calculated
before each swath that the printhead makes over the printing medium.

10 (original): The method of claim 1 wherein M is less than or equal to R+1.
15

11 (original): The method of claim 1, wherein the inkjet printing device is an inkjet
printer having a printhead comprising a plurality of nozzles to jet ink droplets on the
printing medium so as to form the image on the printing medium.

20 12 (original): The method of claim 1, wherein the data representative of the original
image is gray-scale image data.

13 (original): The method of claim 1, wherein the data representative of the original
image is color image data.
25

14 (new): A method of printing an image on a printing medium with an inkjet printing
device, the method comprising:
providing data representative of an original image;

Appl. No. 10/605,501
Amdt. dated November 10, 2005
Reply to Office action of August 15, 2005

- calculating a total heat weighting value for the original image to indicate a degree of heat accumulation for the original image;
- comparing the total heat weighting value to R distinct reference values, R being an integer greater than or equal to one;
- 5 selecting M image masks to be used to mask the original image, wherein a value of M is chosen according to comparison results between the total heat weighting value and the R reference values, M being an integer greater than or equal to one, a first image mask being generated by:
- (b1) choosing contiguous groups of N nozzles to be included in a first mask,
- 10 wherein each group of N nozzles included in the first mask is separated by (M-1)*N nozzles not included in the first mask, N being an integer greater than or equal to one;
- masking the original image with the M image masks to produce M sub-images; and
- printing the M sub-images successively on the printing medium with a plurality of
- 15 nozzles for superimposing the M sub-images on the printing medium, whereby the original image is printed on the printing medium.
- 15 (new): The method of claim 14, wherein the second through Mth masks are generated by:
- 20 (b2) repeating step (b1) for selecting a second mask through an (M-1)th mask, wherein nozzles that were previously chosen to be included in other masks are not included in any additional masks; and
- (b3) choosing all remaining nozzles to be included in an Mth mask.
- 25 16 (new): A method of printing an image on a printing medium with an inkjet printing device, the method comprising:
- providing data representative of an original image;
- calculating a total heat weighting value for the original image to indicate a degree of

Appl. No. 10/605,501
Amdt. dated November 10, 2005
Reply to Office action of August 15, 2005

heat accumulation for the original image;
comparing the total heat weighting value to R distinct reference values, R being an
integer greater than or equal to one;
selecting M image masks to be used to mask the original image, wherein a value of
5 M is chosen according to comparison results between the total heat weighting
value and the R reference values, M being an integer greater than or equal to
one, a first image mask being generated by:
(c1) choosing a current nozzle to be included in the first mask;
(c2) analyzing a group of M nozzles closest to the current nozzle, wherein the
10 group of M nozzles have not been previously chosen or analyzed for
inclusion in the first mask;
(c3) selecting among the group of M closest nozzles a next nozzle which is
farthest away from the current nozzle, and choosing the next nozzle to be
included in the first mask; and
15 (c4) repeating steps (c2) and (c3) until all nozzles have been analyzed, wherein
each next nozzle is treated as the current nozzle after the next nozzle has
been chosen to be included in the first mask;
masking the original image with the M image masks to produce M sub-images; and
printing the M sub-images successively on the printing medium with a plurality of
20 nozzles for superimposing the M sub-images on the printing medium, whereby
the original image is printed on the printing medium.

17 (new): The method of claim 16, wherein the second through Mth masks are generated
by:

25 (c5) repeating steps (c1) through (c4) for selecting a second mask through an
(M-1)th mask, wherein nozzles that were previously chosen to be included in
other masks are not analyzed for inclusion in any additional masks; and
(c6) choosing all remaining nozzles to be included in an Mth mask.